



### Overview

Model Name	APC Power-Saving Back-UPS Pro 1200, 230V
Includes	CD with software , Qty 2- Detachable IEC Power-Cord , Telephone Cable , USB cable , User Manual , Warranty card
Standard Lead Time	Usually in Stock
Product Distribution	Afghanistan , Albania , Algeria , Andorra , Angola , Antigua And Barbuda , Armenia , Australia , Austria , Azerbaijan , Bahrain , Bangladesh , Belarus , Belgium , Benin , Bhutan , Bolivia , Bosnia And Herzegovina , Botswana , Brunei Darussalam , Bulgaria , Burkina Faso , Burundi , Cambodia , Cameroon , Cayman Islands , Central African Republic , Chad , Chile , Congo , CONGO, THE DEMOCRATIC REPUBLIC OF THE , Cook Islands , <![CDATA[Cote D'Ivoire]]> , Croatia , Cyprus , Czech Republic , Denmark , Djibouti , Dominica , East Timor , Egypt , Equatorial Guinea , Eritrea , Estonia , Ethiopia , Fiji , Finland , France , Gabon , Gambia , Georgia , Germany , Ghana , Gibraltar , Greece , Guadeloupe , Guinea , French Guiana , Hong Kong , Hungary , Iceland , Indonesia , Iran (Islamic Republic Of) , Iraq , Ireland , Israel , Italy , Jordan , Kazakhstan , Kenya , KOREA, REPUBLIC OF , Kuwait , Latvia , Lebanon , Lesotho , Liberia , Liechtenstein , Lithuania , Luxembourg , Macedonia , Malawi , Malaysia , Mali , Malta , Martinique , Mauritania , Moldova , Republic Of , Mongolia , Morocco , Mozambique , Myanmar , Namibia , Nepal , Netherlands , New Zealand , Niger , Nigeria , Norway , Oman , Pakistan , Papua New Guinea , Paraguay , Peru , Philippines , Poland , Portugal , Romania , Russian Federation , Rwanda , Saudi Arabia , Senegal , Sierra Leone , Singapore , Slovakia (Slovak Republic) , Slovenia , Somalia , South Africa , Spain , Sri Lanka , Sudan , Suriname , Sweden , Switzerland , Tajikistan , TANZANIA, UNITED REPUBLIC OF , Thailand , Togo , Tunisia , Turkey , Turkmenistan , Uganda , Ukraine , United Arab Emirates , Uruguay , Uzbekistan , Viet Nam , Western Sahara , Yemen , Zambia , Zimbabwe

### Output

Output Power Capacity	720 Watts / 1200 VA
Max Configurable Power (Watts)	720 Watts / 1200 VA
Nominal Output Voltage	230V
Output Frequency (sync to mains)	50 Hz , 60 Hz
Crest Factor	3 : 1
	Line Interactive
Waveform Type	Stepped approximation to a sinewave
Output Connections	(2) IEC Jumpers (Battery Backup) , (5) IEC 320 C13 (Battery Backup) , (5) IEC 320 C13 (Surge Protection)

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Input

Nominal Input Voltage	230V
Input Frequency	50/60 Hz +/- 3 Hz (auto sensing)
Input Connections	IEC-320 C14
Input voltage range for main operations	176 - 294 V
Input voltage adjustable range for mains operation	156 - 300V
Input Breaker Capacity	10 A

## Batteries & Runtime

Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Typical recharge time	8 hour(s)
Replacement Battery	APCRBC124
RBC Quantity	1

## Communications & Management

Interface Port(s)	Optional Simple Signalling RS232 cable , USB
Control panel	Multi-function LCD status and control console
Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous-tone alarm

## Surge Protection and Filtering

Surge energy rating	441 joules
Filtering	Full time multi-pole noise filtering :10% of IEEE surge let-thgouh : zero clampin-g response time: instantaneous
Data Line Protection	Analog phone line for phone/fax/modem/DSL (RJ-11 connector) , Net-work line - 10/100/1000 Base-T Ethernet (RJ-45 connector)

## Physical

Maximum Height	301.0 mm
Maximum Width	112.0 mm
Maximum Depth	380.0 mm
Net Weight	11.6 kg
Shipping Weight	13.2 kg
Shipping Height	387.0 mm
Shipping Width	238.0 mm
Shipping Depth	488.0 mm
Master Carton Units	1.0
Color	Black
SCC Codes	1073130426875 5
Units per Pallet	24.0

## Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-9000 meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-15000 meters
Audible noise at 1 meter from surface of unit	45.000 dB

## Conformance

Approvals	A-tick , C-tick , CE , GOST , GS Mark , TUV , Telepermit
Standard warranty	2 years repair or replace , 3 years repair or replace for European Union countries
Equipment protection policy	Lifetime : 150000 Euros , Lifetime : 200000 AUD , Lifetime : 75000 GBP

## Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains No SVHCs