

Capacity(VA/Watts)	600 / 360	800 / 480	1000 / 600	1200 / 720	1500 / 900	2000 / 1200	2400 / 1440	3000 / 1800
--------------------	-----------	-----------	------------	------------	------------	-------------	-------------	-------------

#### INPUT

Voltage	220/230/240Vac
Voltage Range	140~300Vac
Frequency Range	50/60Hz (auto sensing)

#### OUTPUT

AC Voltage Regulation (Batt. Mode)	± 10%
Frequency Range (Batt. Mode)	50/60Hz ± 1 Hz
Transfer Time	Typical 4~8ms, 13ms Max.
Waveform (Batt. Mode)	Simulated Sinewave

#### BATTERY

Battery Voltage	12Vdc	24Vdc	48Vdc
Battery Type & Number	12 V / 7Ah x 1	12 V / 9Ah x 1	12 V / 7Ah x 2
Typical Recharge Time	4~6 hours recover to 90% capacity		
	6~8 hours recover to 90% capacity		

#### INDICATORS

LED Display(LED version)	AC Mode, Battery Mode, Overload, Fault	N/A
LCD Display(LCD version)	AC Mode, Battery Mode, Load Level, Battery Level, Input Voltage, Output Voltage, Overload, Fault, and Battery Low	

#### PROTECTION

Full Protection	Short circuit, Overload , Overcharge and overdischarge protection
-----------------	---

#### ALARM

Battery mode	Sounding every 10 seconds
Low Battery	Sounding every second
Overload	Sounding every 0.5 second
Battery Replacement Alarm	Sounding every 2 seconds
Fault	Continuously sounding

#### MANAGEMENT

Communication port	USB or RS232(Supports Windows® 2000/2003/XP/Vista/2008, Windows® 7, Linux, Unix, and MAC)
--------------------	---

#### OPERATING ENVIRONMENT

Humidity	0~90 % RH @ 0~ 40° C (non-condensing)
Noise Level	Less than 45dB
	Less than 55dB

#### PHYSICAL

Approx. Dimension D * W * H (mm)	298*101*142	353*149*162	380*158*198	433*144*207
Approx. Net Weight (kgs)	Approx. 4.3	Approx. 4.9	Approx. 7.8	Approx. 8.4
	Approx. 10.1	Approx. 10.5	Approx. 20	Approx. 23

Specifications are subject to change without prior notice.